



# GasAlert MicroClip XT

multi-gas detector



## Multi-gas made simple

The slim and compact GasAlertMicroClip XT provides affordable protection from atmospheric hazards. With continuous visual confirmation of detector operation and compliance provided by the IntelliFlash™ feature. Simple one-button operation for the ultimate ease of use significantly reduces training times. The GasAlertMicroClip XT is fully compatible with BW's MicroDock II automatic test and calibration system.



H<sub>2</sub>S

CO

O<sub>2</sub>

LEL

- Continuous visual compliance with IntelliFlash
- Multi-gas versatility with one-button simplicity
- Incredibly thin and lightweight, making it comfortable to wear

**WATER  
RESISTANT** 

**BW**  
Technologies  
by Honeywell

**Wear yellow. Work safe.**

### Standard features of BW products:

- Continuous LCD shows real-time gas concentrations
- Compact and lightweight design makes it comfortable to wear
- Water-resistant
- Simple automatic calibration procedure; compatible with BW MicroDock II automatic test and calibration station
- Full function self-test of sensor, battery status, circuit integrity and audible/visual alarms on start up
- Bright wide-angled visual alarm bars
- Built-in concussion-proof boot

<b>GasAlertMicroClip Specifications</b>		
<b>Size</b>	4.4 x 2.4 x 1.1 in. / 11.3 x 6.0 x 2.9 cm	
<b>Weight</b>	6 oz. / 171 g	
<b>Temperature</b>	-4 to +122°F / -20 to +50°C	
<b>Humidity</b>	0% - 95% RH (non-condensing)	
<b>Alarms</b>	- Visual, vibrating, audible (95 dB) - Low, High, STEL, TWA, OL (over limit)	
<b>Tests</b>	Audible/visual alarms on activation, sensors, battery and circuitry (continuous)	
<b>Pump</b>	Compatible with the Sampler motorized sampling pump	
<b>Typical battery life</b>	10 hours (typical); recharges in less than 4 hours	
<b>User options</b>	Confidence beep	Combustible gas measurement (% LEL or % by volume methane)
	Set STEL interval	User-settable calibration gas level
	Sensor on/off	Force bump test when overdue
	Latching alarms	Force calibration when overdue
	Safe display mode	Low alarm acknowledge
	Stealth mode	Language choices (five)
	Calibration lock	Set custom start up message
	Auto zero on start up	
	O <sub>2</sub> auto calibration on start up	
	Set bump test interval	
	IntelliFlash interval	
<b>Ratings</b>	EMI/RFI: Complies with EMC Directive 89/336/EEC IP 66/67	
<b>Certifications and approvals</b>	<b>CE</b> Class I, Div. 1, Gr. A, B, C, D <b>ATEX:</b> <b>CE</b> II 1 G Ex ia IIC T4 Ga <b>IECEX:</b> Ex ia IIC T4 Ga <b>CE:</b> European Conformity	
<b>Warranty</b>	Full two-year warranty including all sensors	

### Additional GasAlertMicroClip XT features:

- IntelliFlash verifies operation and compliance to both the user and supervisor
- Tamper-proof, one button operation
- Compatible with the Sampler motorized remote sampling pump
- Equipped with internal vibrating alarm for high noise areas
- Powered by a lithium polymer battery
- Multi-language support in English, French, German, Spanish and Portuguese
- Conveniently manage your fleet using Fleet Manager II

### Options and Accessories



MicroDock II compatible



Auxillary filter kit



IR connectivity kit




Five unit cradle charger

For a complete list of accessories, please contact BW Technologies by Honeywell.

<b>Sensor Specifications</b>		
Gas	Measuring Range	Resolution
<b>H<sub>2</sub>S</b>	0-100 ppm	1 ppm
<b>CO</b>	0-500 ppm	1 ppm
<b>O<sub>2</sub></b>	0-30.0%	0.1%
<b>Combustible gases</b>	0-100% LEL 0-5.0% v/v	1% 0.1%
Alarm setpoints for all sensors are user adjustable. Setpoints are automatically displayed during instrument start up.		

### Locally available from



### Corporate Headquarters

2840 - 2 Avenue S.E.  
Calgary, AB, Canada T2A 7X9  
Phone: +1.403.248.9226  
Toll free: 1.800.663.4164

[www.gasmonitors.com](http://www.gasmonitors.com)

USA 1.888.749.8878  
Europe +44 (0)1295.700.300  
France +33 (0) 442.98.17.70  
Germany 49 (0) 2137.17.6522

[info@gasmonitors.com](mailto:info@gasmonitors.com)

Middle East +971.4.450.5852  
S.E. Asia +65.6580.3468  
China +86.10.6786.7305  
Australia +61.3.9464.2770

Latin America +55.11.3309.1030  
Other Countries +1.403.248.9226

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.