



SUBSEA TECHNOLOGY



Mini-Ranger 2 is a sixth-generation (6G) Ultra-Short Baseline (USBL) underwater target tracking system. It offers a standard operating range of 995 metres (extendable up to 4,000 metres) and the ability to simultaneously track up to 10 subsea targets (e.g. divers, ROVs and structures) at very fast update rates. These features mean that Mini-Ranger 2 is ideal for nearshore operations on small, quiet vessels, vessels of opportunity, pipelay and construction barges that need survey grade positioning performance without the cost and complexity of a deep water USBL solution.

SONARDYNE MINI-RANGER 2 USBL UNDERWATER TARGET TRACKING SYSTEM

SYSTEM OVERVIEW

Mini-Ranger 2 calculates the position of an underwater target by measuring the range (distance) and bearing (heading) from a vessel-mounted transceiver to an acoustic transponder fitted to the target; a technique known as Ultra-Short Baseline (USBL) positioning. One of the main advantages of the USBL technique is that no other in-water acoustic equipment has to be deployed before underwater operations can commence. Only the targets being tracked need to be equipped with a transponder.

The Sonardyne 6G and Wideband 2 digital signal technology inside Mini-Ranger 2 USBL offers precise acoustic ranging and hardware that is easier to set up and operate, even in the most challenging subsea operating environments. These features improve the efficiency of subsea survey operations, reduce vessel delays and generate cost savings for owners.

Mini-Ranger 2 is compact and highly portable, comprising the 1U-high (desk or rack-mounted) Ethernet Serial Hub (ESH), HPT 3000 acoustic transceiver and software which is installed on the user's own PC or ruggedised laptop. A wide range of Sonardyne 6G mini transponders can be used with Mini-Ranger 2 allowing the user to select the most appropriate beacon for the task in hand. These include; Wideband Sub-Mini 6+ (WSM 6+), Wideband Release Transponder 6 (WRT 6), Wideband Mini Transponder 6 (WMT 6) and the ultra-small Nano.

WHAT YOU NEED TO KNOW

- Portable and quick to install on all types of vessel
- 0.2% system accuracy when optimised
- 995 metres standard tracking range; exempt from export control for fast, uncomplicated international shipping
- Tracking range extendable up to 4,000 metres depending on operating set up
- Fast target position updates; up to 3 per second
- Automatic discovery and tracking of Sonardyne 6G transponders
- Audio Codec for live listening and recording acoustics
- Audio and visual diagnostic tools enable optimised performance
- Importable DXF chart backdrops

HPT 3000

At the heart of Mini-Ranger 2 is the HPT (High Performance Transceiver) 3000 transceiver. Small and lightweight, HPT 3000 is perfect for installation on very small boats using temporary, over-the-side deployment arrangements.

The transceiver features a unique design of receiver array and transmitter which are optimised to provide excellent performance in shallow water, at high elevations, as well as in deeper water. USBL precision is dependent on the baseline between the receiver elements and signal to noise. This is where the HPT 3000 excels in that the larger diameter array provides excellent precision and noise rejection, dramatically better than USBL systems on the market with much smaller diameter arrays.

A key feature of the HPT 3000 is that communications are all Ethernet based. This means connection to the topside computer (via the Ethernet Serial Hub) is simple and user friendly as it can be connected through a ship's network via a single network socket – eliminating challenging USB to serial drivers and their associated compatibility problems. Ethernet based communications also enable improved in-water diagnostics, allowing the operator to both listen to, and visualise, signals and noise in the water. The HPT 3000 is available in durable Aluminium Bronze or lightweight Aluminium Alloy.

SOFTWARE

Mini-Ranger 2 uses the same modern and intuitive software as Sonardyne's deep water USBL system, Ranger 2, thereby ensuring users quickly become confident in its use. An extensive set of tools are included to allow the user to optimise the system performance, including real-time audio and visual signal and noise analysis displays. Sonardyne's CASIUS calibration tool is also included to correctly calibrate gyro and VRU offsets, and so improve positioning accuracy. There is a built-in calibration routine of the internal magnetic sensor to minimise the time between installation and tracking.

ETHERNET SERIAL HUB

With Mini-Ranger 2, the Ethernet Serial Hub provides a simple, but all-encompassing, robust interface between peripheral sensors, acoustic instruments, mains power and the software running on the PC. Communications are all Ethernet based, allowing connection through a ship's network and eliminating the requirement for all equipment to be co-located on the bridge. The Ethernet Serial Hub also supports responder trigger and 1PPS synchronisation across systems.

Software Mini-Ranger 2 shares the same modern and intuitive interface as Sonardyne's established Ranger 2 USBL system ensuring users quickly become confident in its use.



Global Headquarters

T. +44 (0) 1252 872288
F. +44 (0) 1252 876100
sales@sonardyne.com

Singapore

T. +65 6542 1911
F. +65 6542 6937
asia.sales@sonardyne.com

Aberdeen, UK

T. +44 (0) 1224 707875
F. +44 (0) 1224 707876
sales@sonardyne.com

Rio das Ostras, Brasil

T. +55 22 2123 4950
F. +55 22 2123 4951
brasil.sales@sonardyne.com

Houston, USA

T. +1 281 890 2120
F. +1 281 890 7047
usa.sales@sonardyne.com

24 Hour Emergency Telephone Helpline

T. +44 (0) 1252 877600
support@sonardyne.com



Ethernet Serial Hub and HPT 3000

The Ethernet Serial Hub (ESH) is a 1U-high (desk or rack-mounted) unit for interfacing the HPT 3000 transceiver, GPS and user's PC running the Mini-Ranger 2 software. The HPT 3000 is designed for portable installation on very small boats. It offers excellent performance in shallow water, at high elevations, as well as in deeper water.



Transponder options

Mini-Ranger 2 is compatible with Sonardyne's mini transponders including; WSM 6+ (below left top), Nano (below left bottom), WRT 6 (below right), WMT 6, as well as aircraft pinger locators.

